





**Curtain Track Measure Sheet**

Date of Order: 20/11/23  
 Order Reference: 46871 Pricey  
 Date Required: 4/12/2023

Company Name: Ascension Buss Co  
 Contact: \_\_\_\_\_

Delivery Address: \_\_\_\_\_

Site Contact: Sivan  
 Telephone Number: \_\_\_\_\_

Customer Signature: \_\_\_\_\_

System Number	Colour	Qty	* Child Safety Device (Integral 10483) Y/N	Overall Width	Location	** Installation Height:	Input		Bracket number if known or projection in mm	Method	Wave Tracks please tick
							LH / RH or B	T / F or A			
3000	White	1			1625	2800	both	Top		Pair	<input type="checkbox"/> If face <input type="checkbox"/> 3135 bkt = 60mm <input type="checkbox"/> 3136 bkt = 80mm <input type="checkbox"/> 60mm <input type="checkbox"/> 80mm
				810/121	(121) (121)	2805		18 Runners		Pair	
					Pair STACI						

Please Note: For multiple stack please include diagram  
 60mm Wave uses 3135 bracket as standard  
 80mm wave uses 3136 bracket as standard  
 \* Child Safety Device applicable to System 3840 only complete with Silent Gliss Colorama Wave Curtains only  
 \*\* If the Installation Height is known - cord drops will comply with EN13120  
 \*\*\* If B for both, intermediate pulley will be added at extra cost  
 Child Safety Legislation EN 13120

Operating loop for Child Safety Device	
Installation Height	Chain Length
Known	Distance from floor to bottom of pull cords shall be at least 0.6m
Unknown	Less than or equal to 2/3rd drop of the blind
	Operating loop for chain retainer
	Installation Height
	Known
	Not Known drop < 2.5m
	Not Known drop > 2.5m
	Chain Length
	Distance from floor to bottom of operating chain shall be at least 1.5m
	Length of operating chain loop shall be ≤ 1m
	Shall be ≤ drop of blind less 1.5m