

Curtain Track Measure Sheet

Date of Order: 16/08/24

Company Name: Advanced Truss C

Order Reference: CAW0000
Contact: 488667

Date Required: ASAP

Telephone Number:

Delivery Address:

Telephone Number:

Customer Signature:

[Handwritten Signature]

System Number	Colour	Qty	Overall Width	Location	** Installation Height:	Input		Bracket number if known or projection in mm	Method		Option 1, 2, 3, None	Cord Drop	Wave Tracks please tick	
						LH / RH or B	T / F / A or R		LH / RH / Pair or Centre Stacking	Enhanced Wave			If face 11201 Bkt = 60mm 11202 Bkt = 80mm	
7610 (30mm)	Black	1	3154		1095	BOTH	FACE	640	Pair			<input type="checkbox"/>	<input type="checkbox"/>	
					644			640				<input type="checkbox"/>	<input type="checkbox"/>	
					400			380				<input type="checkbox"/>	<input type="checkbox"/>	

Please Note: For multiple stack please include diagram When Face fixing Wave:

5700 EUR

- * Child Safety Device applicable to System 3840 only - complete with Silent Gliss Colorama Wave Curtains only
- ** If the Installation Height is known - cord drops will comply with EN13120
- *** If B for both, intermediate pulley will be added at extra cost
- **** Enhanced Wave
- Option 1 - 2255 Adjustable Brake
- Option 2 - 2255 Adjustable Brake & 6366 Carrier
- Option 3 - Enhanced Wave (80mm Only)
- ***** Recess Fixing option only on 6465, 6870, 6970, 3870 and 3970 (additional costs apply)

Child Safety Legislation EN 13120	
Operating loop for Child Safety Device	Operating loop for chain retainer
Installation Height	Installation Height
Known	Known
Unknown	Not Known drop ≤ 2.5m
	Not Known drop > 2.5m
	Chain Length
	Distance from floor to bottom of operating chain shall be at least 1.5m
	Length of operating chain loop shall be 31m
	Not Known drop > 2.5m
	Shall be 5 drop of blind less 1.5m