



Rainbow Blinds

Rainbow Blinds & Interiors

61 Canyon Road
Excelsior Park

Waltham
ML2 0EG

T. 01698 391 888
F. 01698 391 999

sales@rainbow-blinds.com

VERTICAL BLINDS

Order Form

Date: 19/6/18

Model: SIMKIN

Address: GOSFORTH

Depth Required:

Telephone:

Email:

Signature:

Purchase Reference No: 332637

Special Instructions:

BLIND SIZE	CONTROLS				OPTIONS		SLAT SIZE				
	Width (mm)	Drop (mm)	Recess or Exact	Child Safety Installation Height (mm)	Length of Control (W/R/D)	Fabric Range	Fabric Colour	Draw	Operator	Headrail Colour	TopFace Fix
1916/18	1854	2403	R	2438	W/R/D	GEMINI	SHOOTER	Draw: RNS (v) ✓, LHS (v) ✓ Operator: RNS (v) ✓, LHS (v) ✓	W	T	89 ✓, 127 ✓

UNLESS OTHERWISE STATED ALL MEASUREMENTS WILL BE TAKEN AS RECESS

Blinds supplied by Rainbow Blinds & Interiors are fitted with an approved Child Safety device

Customer has been advised on (✓) X The Child Safety Regulations (RNS) and the use of child safety devices

Information document applying to operating cords

Rainbow Blinds

ROLLER BLINDS

Order Form

Rainbow Blinds & Interiors
61 Canyon Road
Excelsior Park
Wishaw
ML2 0EG
T. 01698 351 888
F. 01698 351 999
sales@rainbow-blinds.com

61 Canyon Road
Excelsior Park
Wishaw
ML2 0EG

T. 01698 351 888
F. 01698 351 999
sales@rainbow-blinds.com

Date: 19/6/18
Retailer: SIMKINS
Address: GOSFORTH
Date Required:

Telephone:
Email:
Signature:
Purchase Reference No: 332637

Special Instructions
NO SENS BAR

Window	Width (mm)	Drop (mm)	Recess or Fabric size	Child Safety Installation Height (mm)	Length of Control Chain (mm)	Tube Diameter 3mm, 4mm, 45mm	Fabric Range	Fabric Colour	ORDER			
									Price (£)	Qty	TOTAL COST (£)	
1	1660	1016	R	2438	900	32	GEMINI	SHORTBREAD	LHC / RHC	1		
2												
3												
4							D+E					
5												
6												
7												
8												

NOTE: UNLESS OTHERWISE STATED ALL MEASUREMENTS WILL BE TAKEN AS RECESS AND SYSTEM WILL BE LOUVOLITE 3MM. PLEASE SELECT APPROPRIATE TUBE FOR BLIND WITH, DROP OR FABRIC WEIGHT.

Customer has been advised on (✓) The Child Safety Regulations EN1320 and the use of child safety devices

Minimum distances applying to operating cords.