



Sales Callout Sheet

Filler Name .....  
 Name / Company .....  
 Department .....  
 House .....  
 Road Name .....  
 Place .....  
 Post Town .....  
 Post Code .....  
 Source .....  
 Were did you get your name .....  
 A/c .....  
 Ref .....  
 Date Enquiry .....  
 Contact .....  
 Tel. No .....  
 Ext. ....  
 Fax No .....  
 A-Z Ref .....  
 Measure Date <sup>Year</sup> .....  
 Sale By .....  
 Quote No. ....  
 Order No .....  
 Sales Person .....  
 Day to Call .....  
 Time to Call .....  
 Time Called .....  
 Address Verified .....  
 Action Req'd .....  
 Yes / No .....

Comments

Type	Material Code	Width	Drop	Rec	Cont.	Bklt	Location	VERTICAL		ROLLERS				VEN T/R Col	Special Instructions	Price (inc VAT)
								Broth	T/R Col	Slatp	Page Colour	Tin Code	Tin Colour			
P25	660 x 310		ROLL	X	1500		COM									
	670 x 980		680	X	1500		SMDs									
	590 x 220		760	X	1500											
	680 x 990		770	X	1500											
	610 x 220		760	X	1500		RNICE A									
	700 x 990		580	X	1500		SHADE 1									
	590 x 220		760	X	2000											
	680 x 990		660	X	1500											
	550 x 320		640	X	1500											
	550 x 1000															
	590 x 1810															
	570 330															
	570 1000															
	570 330															
	570 1000															

79  
 108  
 64  
 108  
 79  
 198  
 64  
 108  
 64  
 83  
 113  
 64  
 63  
 64  
 63



# Rainbow Blinds

# PLEATED BLINDS

## Order Form

Rainbow Blinds & Interiors

61 Canyon Road  
Excelsior Park

Wishaw

ML2 OEG

T. 01698 351 888

F. 01698 351 999

sales@rainbow-blinds.com

Date:	26-05-20
Retailer:	BALLETTS
Address:	SPENNYMOOR
Date Required:	

Telephone:	
Email:	
Signature:	
Purchase Reference No:	340535 PYLE

Special Instructions

SIDE TENSIONED BLINDS  
3 RAIL SYSTEM  
HANDLE ON MIDDLE RAIL  
FABRIC TO GO 4 ON FIRST HANGERS ON EACH SIDE  
BLINDS TO ROLL DOWN  
Pg 1 of 2

	BLIND SIZE			PROFILE			STYLE		BLIND		CONTROLS					ORDER				
	Window	Width (mm)	Drop (mm)	Exact or Recess	ALU (✓)	UPVC (✓)	WOOD (✓)	FREE HANGING (✓)	ROOF (✓)	FABRIC RANGE & COLOUR	Headtrial Colour	Child Safety Installation Height (mm)	Length of Control Chain (mm)	RHS (✓)	LHS (✓)	Fixing TOP (✓)	FACE (✓)	Price (£)	Qty	TOTAL COST (£)
1	CON	663	330	EX				SIDE TENSIONED		STRETCHED CREAM	WHITE								1	
2	SIDES	662	1000																1	
3	L70	582	240																1	
4	R	673	1000																1	
5		604	240																1	
6		693	1000																1	
7		582	240																1	
8		673	1000																1	

NOTE: UNLESS OTHERWISE STATED ALL MEASUREMENTS WILL BE TAKEN AS RECESS

All blinds supplied by Rainbow Blinds & Interiors are fitted with an approved Child Safety Device

Customer has been advised on (✓):

The Child Safety Regulations EN1320 and the use of child safety devices

Minimum distances applying to operating cords



# Rainbow Blinds

# PLEATED BLINDS

## Order Form

### Rainbow Blinds & Interiors

61 Canyon Road  
 Excelsior Park  
 Wishaw  
 ML2 0EG  
 T. 01698 351 888  
 F. 01698 351 999  
 sales@rainbow-blinds.com

Date: 26-05-20

Retailer: BAILEYS

Address: SPENNYMOOR

Date Required:

Telephone:

Email:

Signature:

Purchase Reference No: 340535 PYLE

Special Instructions  
 SEE PAGE 1  
 \* ALL BLINDS  
 TO OPERATE  
 BY PULLING  
 DOWN TO  
 OPEN  
 Page 2 of 2

	BLIND SIZE			PROFILE			STYLE		BLIND		CONTROLS					ORDER			
	Window	Width (mm)	Drop (mm)	Exact or Recess	ALU (✓)	UPVC (✓)	WOOD (✓)	FREE HANGING (✓)	ROOF (✓)	FABRIC RANGE & COLOUR	Headrail Colour	Child Safety Installation Height (mm)	Length of Control Chain (mm)	RHS (✓)	LHS (✓)	Fixing TOP FACE (✓)	Price (£)	Qty	TOTAL COST (£)
1	CON	547	330	EX				SIDE	STRATEGIC	WHITE								1	
2	SIDE	548	1000					TENSIONED	CREAM									1	
3	L70	585	1810					BLINDS										1	
4	R	570	330					3 RAIL										1	
5		570	1000					SYSTEM										1	
6		572	330															1	
7		572	1000						CAZEN									1	
8																			

NOTE: UNLESS OTHERWISE STATED ALL MEASUREMENTS WILL BE TAKEN AS RECESS

All blinds supplied by Rainbow Blinds & Interiors are fitted with an approved Child Safety Device

Customer has been advised on (✓):

The Child Safety Regulations EN13240 and the use of child safety devices

Minimum distances applying to operating cords