

Please send to:

order@markilux.com

Your contact	Reference	Customer no.	Order date	Requested delivery date (despatch date)
--------------	-----------	--------------	------------	---

On the basis of your terms and conditions for markilux awnings we hereby place the following order:

Vertical roller blind	Reference	Guide system	Quantity	Overall awning width M [cm]	Extension H [cm]	Frame colour <b>K</b>
<b>markilux 710</b>	9710	cables				
<b>markilux 730</b>	9730	drop arms			arm length 80 <input type="radio"/> 100 <input type="radio"/> 120 <input type="radio"/> 15 <input type="radio"/> cover length 160 <input type="radio"/> 200 <input type="radio"/> 250 <input type="radio"/> 250 <input type="radio"/>	<input type="radio"/>
<b>markilux 740</b>	9740	guide rails + drop arms				
<b>markilux 620 tracfix</b>	9620	guide rails				
<b>markilux 625 tracfix</b>	9625	guide rails				

(markilux 620 / 625 tracfix including hard-wired motor)

**K** Improved corrosion protection**Fabric pattern****Operation side (as viewed from the outside)** left  right **Radio-controlled motor io, 868 MHz** **radio-controlled motor io, 868 MHz with sundrive** 

(only for markilux 620 tracfix – max. blind with 250 cm, max. unit height 300 cm)

hand-held RTS radio remote control 

markilux io-1 designcontrol (1 channel)

markilux io-5 designcontrol (5-channel) with dimmer and light sensor on / off function **Radio-controlled motor RTS, 433 MHz** **radio-controlled motor RTS, 433 MHz with sundrive** 

(only for markilux 620 tracfix – max. blind with 250 cm, max. unit height 300 cm)

hand-held RTS radio remote control 

1 channel Situo 1 RTS Pure (markilux)

5 channel Situo 5 RTS Pure (markilux) with dimmer and light sensor on / off function **Hard-wired motor** **Power supply cable with Hirschmann plug connector** 5m  10m <sup>1)</sup> <sup>1)</sup> only available for radio-controlled motors**Cable exit point (surcharge and possibilities depending on the model, see catalogue)**underneath  at the back  on top  at the front  to the side <sup>2)</sup>**Manual operation**Crank handle length 110 cm  140 cm  160 cm  180 cm  220 cm gearbox exit point at / operation from the rear winding handle for interior operation <sup>2)</sup> markilux 730 is only available as a motorised version from a width of 401 cm**Notes****Fixture**markilux 710/730 Face fixture <sup>3)</sup>  Top fixture 

markilux 620/625 tracfix

left 8 at the back <sup>3)</sup>  9 side  0 without bore right 8 at the back <sup>3)</sup>  9 side  0 without bore Installation between the posts (with markilux markant / pergola stretch) 

(markilux 625 tracfix)

<sup>3)</sup> standard

If no fixture is specified, we deliver standard

**Dimensions split cover**

(markilux 730, with a width &gt; 400 cm, seen from the outside left)

**Accessories (please refer to the sales manual / price list)**additional angle for lateral arm fixture (markilux 730) additional angle for lateral cassette fixture (pair), (730) wedge-in accro bars (markilux 730) radio control light sensor Sunis WireFree II io 8272086 radio control wind sensor Eolis WireFree io 8272193 radio control light and wind sensor Soliris Sensor RTS 8272089 radio control wind sensor Eolis Sensor RTS 8272090 light and wind sensor Soliris UNO 8272081 **N.B! Please check your order confirmation! We deliver as confirmed, complaints will not be accepted at a later date!**