



**SPECIFICATION**

GLASS SPEC (43.5mm)  
10mm CLEAR TOUGHENED OUTER  
16mm ARGON FILLED CAVITY  
17.5mm TOUGHENED LAMINATED INNER

FRAMEWORK  
ALUMINIUM WINDOW SYSTEM PROFILES.

FINISHES  
ALL VISIBLE METALWORK TO BE POLYESTER  
POWDER COATED TO A MINIMUM OF 60  
MICRONS

COLOUR: RAL 7013

GLASS WARM EDGE SPACERS

FIXINGS  
ALL FIXINGS TO BE B29 AND SUITABLE FOR  
THE STRUCTURE AS SHOWN ON DETAILS

SEALING  
COASTLINE TO PROVIDE PERIMETER  
SILICONE SEALS, INCLUDING STRUCTURAL  
SILICONE BONDING OF GLASS INTO FRAME.

REV	DATE	DESCRIPTION OF REVISION	SDR	DRN	CHK
B	08.12.25	UPDATED - SUBJECT TO SITE SURVEY	SDR		
A	05.09.25	FIRST ISSUE - SUBJECT TO SITE SURVEY	SDR		

**APPROVAL**

DO NOT SCALE FROM THIS DRAWING

WE RESERVE THE RIGHT TO ALTER OR AMEND THE SPECIFICATION AND DESCRIPTION GIVEN ON THIS DRAWING IN THE LIGHT OF TECHNICAL DEVELOPMENT AND AVAILABILITY OF MATERIALS

PLEASE NOTE:  
Do not scale from this drawing  
All dimensions are in millimetres unless stated otherwise  
All drawings in 1st Angle Projection unless stated otherwise



CLIENT	AP CONSTRUCTION
CONTRACT TITLE	TIRITEA
DRAWING TITLE	ROOFLIGHT
RF01	
DRAWN BY	SCALE
SI DRIVER	1:20 1:2 @ A3
DATE	05.09.25
DRAWING NO	TIRITEA_RF01
STATUS	APPROVAL
REV	B