

Please send to:

order@markilux.com

Your contact	Reference	Customer no.	Order date	Requested delivery date (despatch date)
--------------	-----------	--------------	------------	---

On the basis of your terms and conditions for markilux awnings we hereby place the following order:

Model	Quantity	stretch	Overall width M [cm]	Extension H [cm]						Frame colour	End caps in polished chrome	K
				150	200	250	300	350	400			
markilux 990 9307		–		<input type="radio"/>	<input type="radio"/>	<input type="radio"/>	<input type="radio"/>	–	–		<input type="radio"/>	<input type="radio"/>
markilux 5010 9540		–		<input type="radio"/>	<input type="radio"/>	<input type="radio"/>	<input type="radio"/>	<input type="radio"/>	<input type="radio"/>		<input type="radio"/>	
markilux 6000 9530		–		<input type="radio"/>	<input type="radio"/>	<input type="radio"/>	<input type="radio"/>	<input type="radio"/>	<input type="radio"/>		<input type="radio"/>	
markilux 3300 9365		–		<input type="radio"/>	<input type="radio"/>	<input type="radio"/>	<input type="radio"/>	<input type="radio"/>	<input type="radio"/>		<input type="radio"/>	
markilux 1710 9565		<input type="radio"/>		<input type="radio"/>	<input type="radio"/>	<input type="radio"/>	<input type="radio"/>	<input type="radio"/>	<input type="radio"/>		<input type="radio"/>	
markilux 1600 9325		<input type="radio"/>		<input type="radio"/>	<input type="radio"/>	<input type="radio"/>	<input type="radio"/>	<input type="radio"/>	<input type="radio"/>		<input type="radio"/>	

including radio-controlled motor io + remote markilux io designcontrol

K Improved corrosion protection

Fabric pattern

valance style (1, 2, 3 or 6)

Operation side (as viewed from the outside) left right

Radio-controlled motor io, 868 MHz

with manual override (only for the markilux 6000, 5010, 990, 1600)

Radio remote control markilux io-1 designcontrol (1 channel)

markilux io-5 designcontrol (5-channel)

Amy 1 io radio transmitter with frame 20100034

Radio transmitter Amy 1 A/M Mode io with frame 20100035

Radio transmitter Amy 4 Mode io with frame 20100036

Somfy Sunteis Solar IO 20100033

Light and wind sensor Soliris Smoove Uno Pure 8272370

Somfy rain sensor Ondeis 230 V AC 8272065

Hard-wired motor

Extended power supply cable 5 m ²⁾ 10 m ³⁾

in the case of silentec / radio-controlled motor io with manual override - separate cable with connector

2) and plug

3) not in the case of silentec / radio-controlled motor io with manual override

Manual operation (not available for the markilux 1650)

Crank handle length [cm] 113 143 163 183 223

spring-assisted operation

Notes

Coupled awnings

field width distribution (as seen from outside and from left to right)

1	2	3	Overall awning width [cm]
---	---	---	---------------------------

Fixture

Face fixture bracket Supply brackets in advance

spreader plate a b

top fixture brackets

eaves fixture brackets additional spreader / backing plate (75383.)

Options

Bionic tendon (markilux 5010, 1600, 1650, 990)

end cap insert in stainless steel mesh (markilux 6000)

LED-Spots, dimmable, with integrated radio receiver (markilux 6000) io ZigBee

Shadeplus [height cm] Hard-wired m ⁵⁾ Gearbox operation

markilux 6000 210 ^{4a)} 210 ^{4a)}

markilux 5010 – 210 ^{4b)}

markilux 1600 10 ^{4c)} 210 ^{4d)}

Operation side (in case of differing) left right

fabric pattern (if it differs from the awning): please refer to the sales manual / price list

4) in the case of vuscreen ALU: a) 170 cm b) 190 cm c) not available d) 100 cm 5) Operation same as awning motor

Additional accessories

wall sealing profile (76385.)

spacer plates (thickness) [number] 12mm 20 mm

for markilux syncra for markilux planet

N.B! Please check your order confirmation! We deliver as confirmed, complaints will not be accepted at a later date!