

## Order confirmation

<b>Order confirmation</b>	13.01.2021	CP Interiors
<b>Order number</b>	1190	St. Saviour
<b>Customer number</b>	1001334	28 Rue des Pres. Tr. Est.
<b>Your VAT number</b>		JE2 7QN JERSEY
<b>Currency</b>	GBP	JERSEY
<b>Project reference</b>	SO10420 Prosser	
<b>Order reference</b>	SO10420 Prosser	
<b>Latest delivery date</b>	19.04.2021	

**Incoterms** DAP  
Jersey

**Delivery address**

CP Interiors  
St. Saviour  
28 Rue des Pres. Tr. Est.  
JE2 7QN JERSEY  
JERSEY

### Overview

Material	Quantity	Net amount	VAT %
001000 CAM2 CAMARGUE	1,00 PC	18.423,00	
<b>Total before VAT</b>		<b>18.423,00</b>	
<b>VAT</b>		<b>0,00</b>	
<b>Total incl. VAT</b>		<b>18.423,00</b>	

For questions or remarks regarding this document, please send an email to [louise.pype@renson.be](mailto:louise.pype@renson.be)

The General Terms and Conditions of Sale are integral part of our agreement. See Professional Portal at <http://www.renson.eu/>

## Order confirmation

1190

13.01.2021

### Detail

Item	Material	Unit price	Quantity	Gross amount	Discount %	Net amount
001000	CAM2 CAMARGUE		1,00 PC	30.705,00		18.423,00
	Commodity code	94069090	Prefabricated buildings, whether or not complete or already assembled (excl. mobile homes a			
	Camargue	13.169,00 GBP /	1 PC x 1,00	13.169,00		
	Camargue Line column	419,00 GBP /	1 PC x 4,00	1.676,00		
				<b>14.845,00</b>	<b>40</b>	<b>8.907,00</b>
	Integrated Fixscreen	1.908,00 GBP /	1 PC x 2,00	3.816,00		
	Integrated Fixscreen	2.243,00 GBP /	1 PC x 2,00	4.486,00		
				<b>8.302,00</b>	<b>40</b>	<b>4.981,20</b>
	3 Lineo Led	2.239,00 GBP /	1 PC x 1,00	2.239,00		
				<b>2.239,00</b>	<b>40</b>	<b>1.343,40</b>
	UpDown Led : 2x Up RGB	2.043,00 GBP /	1 PC x 1,00	2.043,00		
				<b>2.043,00</b>	<b>40</b>	<b>1.225,80</b>
	2 Heats	2.452,00 GBP /	1 PC x 1,00	2.452,00		
	Heating receiver	309,00 GBP /	1 PC x 2,00	618,00		
				<b>3.070,00</b>	<b>40</b>	<b>1.842,00</b>
	Telis 16 RTS Pure - 16-channel transmitter	206,00 GBP /	1 PC x 1,00	206,00		
				<b>206,00</b>	<b>40</b>	<b>123,60</b>
				<b>15.860,00</b>		<b>9.516,00</b>
	<b>Configuration</b>					
	<b>Structure</b>					
	<b>Type</b>					
	<b>Structure</b> Single					
	<b>Strength requirements</b>					
	Location Normal wind loads (standard)					
	Structure strength Standard					
	<b>Construction</b>					
	<b>Type</b>					
	Roof part Roof part 1					
	<b>Dimensions</b>					
	Span 4.250 mm					
	Pivot 5.200 mm					
	Passage height 2.300 mm					
	<b>Construction</b>					
	Span 1 Freestanding					
	Span 2 Freestanding					
	Pivot 1 Freestanding					
	Pivot 2 Freestanding					
	<b>Columns</b>					
	Column type 1A Corner column					
	Column type 1B Corner column					
	Column type 2A Corner column					
	Column type 2B Corner column					
	<b>Side infills</b>					
	<b>Span 1 (S1)</b>					
	Infill S1 Fixscreen					
	<b>Span 2 (S2)</b>					
	Infill S2 Fixscreen					

## Order confirmation

1190

13.01.2021

<b>Pivot 1 (P1)</b>	
Infill P1	Fixscreen
<b>Pivot 2 (P2)</b>	
Infill P2	Fixscreen
<b>Comfort</b>	
<b>Lighting</b>	
Number of Lineo LED	3
Color Lineo LED	Warm white
Position UpDown led	Span 1 + 2
Color led 'UP'	RGB
<b>Comfort &amp; Design</b>	
Beam Heat & Sound on side P2	2 Heats
Somfy Heating Receiver	RTS receiver
<b>Automation</b>	
Motor control	Somfy RTS
Transmitter	Telis 16 RTS Pure white
Voltage motor	230V
Electrical certification	CE (Standard)
<b>Styling</b>	
<b>Colors</b>	
Color type frame	Textured
Color code frame	029/80303-TIGER RAL9005 FINE TEXTURE
Color blades	Textured
Color blades	029/10797-TIGER BIANCO 02 BEL9010 FINE TEXTURE
<b>Type of fabrics</b>	
Type of fabric Fixscreen	Fibreglass fabric Sergé
Fabric code Fixscreen	FG-SC 2020 LINEN
Confection side	Confection side 1
<b>Technical specs</b>	
<b>General</b>	
Motor position	Pivot 2 (P2)
Blade rotation	Sunprotection
<b>Columns</b>	
Mounting base 1A	Invisible mounting base
Mounting holes in the col. 1A	Yes
Direction of water drainage 1A	Pivot
Height water drainage 1A	66 mm/ 2.60" + overlength
Mounting base 1B	Invisible mounting base
Mounting holes in the col. 1B	Yes
Mounting base 2A	Invisible mounting base
Mounting holes in the col. 2A	Yes
Water drainage direction 2A	Pivot
Height water drainage 2A	66 mm/ 2.60" + overlength
Mounting base 2B	Invisible mounting base
Mounting holes in the col. 2B	Yes