

Order confirmation

Confirmation date	07.11.2022	CP Interiors
Order number	20980	St. Saviour
Customer number	1001334	28 Rue des Pres. Tr. Est.
Your VAT number		JE2 7QN JERSEY
Currency	GBP	JERSEY
Project reference	Dwyer SO13334 final measure	
Order reference	DWYER SO13334	
Latest delivery date	17.01.2023	

Incoterms DAP
Jersey

Delivery address

CP Interiors
St. Saviour
28 Rue des Pres. Tr. Est.
JE2 7QN JERSEY
JERSEY

Overview

Material	Quantity	Net amount	VAT %
001000 CAM2 CAMARGUE	1,00 PC	19.337,51	
Total before VAT		19.337,51	
VAT		0,00	
Total incl. VAT		19.337,51	

Free of VAT, export

PAYMENT INFORMATION

Payment term 30 days end of month

For questions or remarks regarding this document, please send an email to outdoor-uk@renson.be

The General Terms and Conditions of Sale are integral part of our agreement. See Professional Portal at <http://www.renson.eu/>

Order confirmation

20980

07.11.2022

Detail

Item	Material	Unit price	Quantity	Gross amount	Discount %	Net amount
001000	CAM2 CAMARGUE		1,00 PC	32.229,18		19.337,51
	Commodity code	94069090	Prefabricated aluminum buildings, sun protection structures			
	Camargue	13.950,00 GBP /	1 PC x 1,00	13.950,00		
	Camargue Line column	522,00 GBP /	1 PC x 3,00	1.566,00		
	Camargue Line reinforced mounting base	208,00 GBP /	1 PC x 3,00	624,00		
				16.140,00	40	9.684,00
	Integrated Fixscreen	2.783,00 GBP /	1 PC x 1,00	2.783,00		
				2.783,00	40	1.669,80
	Glass sliding panels	2.964,00 GBP /	1 PC x 1,00	2.964,00		
	Glass sliding panels	4.699,00 GBP /	1 PC x 1,00	4.699,00		
	Rubber sealing	37,00 GBP /	1 PC x 9,00	333,00		
				7.996,00	40	4.797,60
	UpDown Led : 2x Up RGB + Down White	2.493,00 GBP /	1 PC x 1,00	2.493,00		
				2.493,00	40	1.495,80
	Protecto	1.125,00 GBP /	1 PC x 1,00	1.125,00		
	Rain sensor	236,86 GBP /	1 PC x 1,00	236,86		
	Situo 5 IO Pure II - 5-channel transmitter	90,32 GBP /	1 PC x 1,00	90,32		
	Tahoma	198,00 GBP /	1 PC x 1,00	198,00		
	Watertight wall connection (installation profile)	417,00 GBP /	1 PC x 1,00	417,00		
	Watertight wall connection (installation profile)	750,00 GBP /	1 PC x 1,00	750,00		
				2.817,18	40	1.690,31
				16.089,18		9.653,51
	Configuration					
	Structure					
	Type					
	Structure			Single		
	Location					
	Location			Normal wind loads (standard)		
	Structure strength			Standard		
	Construction					
	Type					
	Roof part			Roof part 1		
	Dimensions					
	Span			2.940 mm		
	Pivot			5.400 mm		
	Passage height			2.340 mm		
	Construction method					
	Span 1			Full wall		
	Span 2			Freestanding		
	Pivot 1			Freestanding		
	Pivot 2			Full wall		
	Columns					
	Column type 1A			Corner column		
	Column type 1B			Corner column		
	Column type 2A			Corner column		
	Design Styles (TL)					
	Design Styles (SL)					

Order confirmation

20980

07.11.2022

Design Style	No
Side infills	
Span 2 (S2)	
Infill S2	Glass sliding panels
Opening direction S2	Opening right to left
Height glass sliding panels S2	Passage height
Pivot 1 (P1)	
Infill P1	Glass panels & Fixscreen
Opening direction P1	Sliding open from the middle
Height glass sliding panels P1	Passage height
General specifications	
Infill height Fixscreen	Passage height
Glass included	Yes
Type glas	Clear glass
Sealing for glass panels	Yes
Comfort	
Lighting	
Position UpDown led	Pivot 1 + 2
Color led 'UP'	RGB
Color led 'DOWN'	Warm white
Comfort & Design	
Protecto on roof part 1	Yes
Protecto side	P1 & P2
Waterproof wall connection	Yes
Automation	
Country of installation	United Kingdom
Motor control	Somfy IO
Renson Connect App	Yes
Frost/Snow function	No
Transmitter	Situo 5 IO Pure II
Rain sensor	Ceramic rain sensor
Voltage motor	230V
Electrical certification	CE (Standard)
Is there a Tahoma account	No
Styling	
Colors	
Color type frame and columns	Textured
Color code frame and columns	068/71764-TIGER RAL7021 TEXTURE
Color type of roof blades	Matt
Color of roof blades	AE20107226021-AXALTA RAL9007 MATT SMOOTH
Type of fabrics	
Type of fabric Fixscreen	Fibreglass fabric Sergé
Fabric code Fixscreen	FG-SC 0130 GREY-CHARCOAL
Confection side	Confection side 1
Technical specs	
General	
Motor position	Pivot 2 (P2)
Blade rotation	Indirect sunlight
Columns	
Mounting base 1A	Invisible reinforced
Mounting holes in the col. 1A	Yes
Direction of water drainage 1A	Pivot
Height water drainage 1A	66 mm/ 2.60" + overlength
Mounting base 1B	Invisible reinforced



Creating healthy spaces

NV Renson® Sunprotection-Screens SA

Order confirmation

20980

07.11.2022

Mounting holes in the col. 1B

No

Mounting base 2A

Invisible reinforced

Mounting holes in the col. 2A

No
