

Quotation

Quotation date	10.06.2022	CP Interiors
Quotation number	20042630	St. Saviour
Customer number	1001334	28 Rue des Pres. Tr. Est.
Your VAT number		JE2 7QN JERSEY
Currency	GBP	JERSEY
Project reference	Philip SO13339	
Order reference	SO13339	
Validity from-to	10.06.2022 - 10.07.2022	

Incoterms	DAP Jersey	Delivery address CP Interiors St. Saviour 28 Rue des Pres. Tr. Est. JE2 7QN JERSEY JERSEY
------------------	---------------	---

Overview

	Material	Quantity	Net amount	VAT %
001000	CAM2 CAMARGUE	1,00 PC	11.442,71	
002000	CAM2 CAMARGUE	1,00 PC	9.864,52	
003000	CAM2 CAMARGUE	1,00 PC	10.837,72	
004000	CAM2 CAMARGUE	1,00 PC	12.415,91	
Total before VAT			44.560,86	
VAT			0,00	
Total incl. VAT			44.560,86	

The General Terms and Conditions of Sale are integral part of our agreement. See Professional Portal at <http://www.renson.eu/>



Creating healthy spaces

NV RENSON® Sunprotection-Screens SA

Quotation

20042630

10.06.2022

Free of VAT, export

PAYMENT INFORMATION

Payment term

30 days end of month

For questions or remarks regarding this document, please send an email to george.bishar@renson.be

The General Terms and Conditions of Sale are integral part of our agreement. See Professional Portal at <http://www.renson.eu/>

NV RENSON® Sunprotection-Screens SA • IZ 1 Flanders Fields • Kalkhoevestraat 45 • B-8790 Waregem
+3256627111 • info@renson.eu • www.renson.eu

VAT BE 0432.549.526 • RPR Gent, afdeling Kortrijk • ING BELGIË IBAN BE08 3850 3006 5013 - BIC BBRUBEBB

Quotation

20042630

10.06.2022

Detail

Item	Material	Unit price	Quantity	Gross amount	Discount %	Net amount
001000	CAM2 CAMARGUE		1,00 PC	19.071,18		11.442,71
	Commodity code	94069090	Prefabricated aluminum buildings, sun protection structures			
	Camargue	11.094,00 GBP /	1 PC x 1,00	11.094,00		
	Camargue Line column	550,00 GBP /	1 PC x 3,00	1.650,00		
	Camargue Line reinforced mounting base	208,00 GBP /	1 PC x 3,00	624,00		
				13.368,00	40	8.020,80
	Integrated Fixscreen	1.782,00 GBP /	1 PC x 1,00	1.782,00		
	Integrated Fixscreen	1.983,00 GBP /	1 PC x 1,00	1.983,00		
				3.765,00	40	2.259,00
	Protecto	1.126,00 GBP /	1 PC x 1,00	1.126,00		
	Rain sensor	236,86 GBP /	1 PC x 1,00	236,86		
	Situo 5 IO Pure II - 5-channel transmitter	90,32 GBP /	1 PC x 1,00	90,32		
	Watertight wall connection (installation profile)	485,00 GBP /	1 PC x 1,00	485,00		
				1.938,18	40	1.162,91
				5.703,18		3.421,91

Configuration

Structure

Type

Structure

2-parts coupled at pivot side

Location

Location

Normal wind loads (standard)

Structure strength

Standard

Construction

Type

Roof part

Roof part 1

Dimensions

Span

3.500 mm

Pivot

2.900 mm

Passage height

2.600 mm

Construction method

Span 1

Freestanding

Span 2

Full wall

Pivot 1

Freestanding

Pivot 2

Connection beam

Columns

Column type 1A

Corner column

Column type 2A

Corner column

Column type 2B

Corner column

Design Styles (TL)

Design Styles (SL)

Design Style

No

Side infills

Span 1 (S1)

Infill S1

Fixscreen

Pivot 1 (P1)

Infill P1

Fixscreen

Comfort

Quotation

20042630

10.06.2022

3.830,86

2.298,52

Configuration

Structure

Type

Structure

2-parts coupled at pivot side

Location

Location

Normal wind loads (standard)

Structure strength

Standard

Construction

Type

Roof part

Roof part 2

Dimensions

Span

3.500 mm

Pivot

2.900 mm

Passage height

2.600 mm

Construction method

Span 1

Freestanding

Span 2

Full wall

Pivot 1

Coupled to connection beam

Pivot 2

Freestanding

Columns

Column type 1B

Corner column

Column type 2B

Corner column

Design Styles (TL)

Design Styles (SL)

Design Style

No

Side infills

Span 1 (S1)

Infill S1

Fixscreen

Comfort

Comfort & Design

Protecto on roof part 1

Yes

Protecto side

P1 & P2

Waterproof wall connection

Yes

Automation

Country of installation

United Kingdom

Motor control

Somfy IO

Rain sensor

Ceramic rain sensor

Voltage motor

230V

Electrical certification

CE (Standard)

Styling

Colors

Color type frame and columns

Textured

Color code frame and columns

AE03057702420-AXALTA RAL7024 FINE TEXTURE

Color type of blades

Same color as framework

Color blades

AE03057702420-AXALTA RAL7024 FINE TEXTURE

Type of fabrics

Type of fabric Fixscreen

Fibreglass fabric Sergé

Fabric code Fixscreen

FG-SC 3030 CHARCOAL

Confection side

Confection side 1

Technical specs

General

Motor position

Pivot 1 (P1)

Quotation

20042630

10.06.2022

Blade rotation	Sunprotection
Columns	
Mounting base 1B	Invisible reinforced
Mounting holes in the col. 1B	Yes
Water drainage direction 1B	Pivot
Height water drainage 1B	66 mm
Mounting base 2B	Invisible reinforced
Mounting holes in the col. 2B	Yes
Water drainage direction 2B	Pivot
Height water drainage 2B	66 mm

003000 CAM2 1,00 PC 18.062,86 10.837,72

CAMARGUE

Commodity code 94069090

Prefabricated aluminum buildings, sun protection structures

Camargue	12.317,00	GBP	/	1	PC	x	1,00	12.317,00		
Camargue Line column	550,00	GBP	/	1	PC	x	2,00	1.100,00		
Camargue Line reinforced mounting base	208,00	GBP	/	1	PC	x	2,00	416,00		
								13.833,00	40	8.299,80
Integrated Fixscreen	2.283,00	GBP	/	1	PC	x	1,00	2.283,00		
								2.283,00	40	1.369,80
Protecto	1.126,00	GBP	/	1	PC	x	1,00	1.126,00		
Rain sensor	236,86	GBP	/	1	PC	x	1,00	236,86		
Watertight wall connection (installation profile)	584,00	GBP	/	1	PC	x	1,00	584,00		
								1.946,86	40	1.168,12
								4.229,86		2.537,92

Configuration

Structure

Type

Structure

2-parts coupled at pivot side

Location

Location

Normal wind loads (standard)

Structure strength

Standard

Construction

Type

Roof part

Roof part 2

Dimensions

Span

4.150 mm

Pivot

2.900 mm

Passage height

2.600 mm

Construction method

Span 1

Freestanding

Span 2

Full wall

Pivot 1

Coupled to connection beam

Pivot 2

Freestanding

Columns

Column type 1B

Corner column

Column type 2B

Corner column

Design Styles (TL)

Design Styles (SL)

Design Style

No

Side infills

Span 1 (S1)

Infill S1

Fixscreen

Quotation

20042630

10.06.2022

Comfort

Comfort & Design

Protecto on roof part 1	Yes
Protecto side	P1 & P2
Waterproof wall connection	Yes

Automation

Country of installation	United Kingdom
Motor control	Somfy IO
Rain sensor	Ceramic rain sensor
Voltage motor	230V
Electrical certification	CE (Standard)

Styling

Colors

Color type frame and columns	Textured
Color code frame and columns	AE03057702420-AXALTA RAL7024 FINE TEXTURE
Color type of blades	Same color as framework
Color blades	AE03057702420-AXALTA RAL7024 FINE TEXTURE

Type of fabrics

Type of fabric Fixscreen	Fibreglass fabric Sergé
Fabric code Fixscreen	FG-SC 3030 CHARCOAL
Confection side	Confection side 1

Technical specs

General

Motor position	Pivot 1 (P1)
Blade rotation	Sunprotection

Columns

Mounting base 1B	Invisible reinforced
Mounting holes in the col. 1B	Yes
Water drainage direction 1B	Pivot
Height water drainage 1B	66 mm
Mounting base 2B	Invisible reinforced
Mounting holes in the col. 2B	Yes
Water drainage direction 2B	Pivot
Height water drainage 2B	66 mm

004000 CAM2 1,00 PC 20.693,18 12.415,91

CAMARGUE

Commodity code 94069090

Prefabricated aluminum buildings, sun protection structures

Camargue	12.317,00	GBP	/	1	PC	x	1,00	12.317,00		
Camargue Line column	550,00	GBP	/	1	PC	x	3,00	1.650,00		
Camargue Line reinforced mounting base	208,00	GBP	/	1	PC	x	3,00	624,00		
								14.591,00	40	8.754,60
Integrated Fixscreen	1.782,00	GBP	/	1	PC	x	1,00	1.782,00		
Integrated Fixscreen	2.283,00	GBP	/	1	PC	x	1,00	2.283,00		
								4.065,00	40	2.439,00
Protecto	1.126,00	GBP	/	1	PC	x	1,00	1.126,00		
Rain sensor	236,86	GBP	/	1	PC	x	1,00	236,86		
Situo 5 IO Pure II - 5-channel transmitter	90,32	GBP	/	1	PC	x	1,00	90,32		
Watertight wall connection (installation profile)	584,00	GBP	/	1	PC	x	1,00	584,00		
								2.037,18	40	1.222,31
								6.102,18		3.661,31

Configuration

Structure

Quotation

20042630

10.06.2022

Type	
Structure	2-parts coupled at pivot side
Location	
Location	Normal wind loads (standard)
Structure strength	Standard
Construction	
Type	
Roof part	Roof part 1
Dimensions	
Span	4.150 mm
Pivot	2.900 mm
Passage height	2.600 mm
Construction method	
Span 1	Freestanding
Span 2	Full wall
Pivot 1	Freestanding
Pivot 2	Connection beam
Columns	
Column type 1A	Corner column
Column type 2A	Corner column
Column type 2B	Corner column
Design Styles (TL)	
Design Styles (SL)	
Design Style	No
Side infills	
Span 1 (S1)	
Infill S1	Fixscreen
Pivot 1 (P1)	
Infill P1	Fixscreen
Comfort	
Comfort & Design	
Protecto on roof part 1	Yes
Protecto side	P1 & P2
Waterproof wall connection	Yes
Automation	
Country of installation	United Kingdom
Motor control	Somfy IO
Renson Connect App	No
Frost/Snow function	No
Transmitter	Situo 5 IO Pure II
Rain sensor	Ceramic rain sensor
Voltage motor	230V
Electrical certification	CE (Standard)
Styling	
Colors	
Color type frame and columns	Textured
Color code frame and columns	AE03057702420-AXALTA RAL7024 FINE TEXTURE
Color type of blades	Same color as framework
Color blades	AE03057702420-AXALTA RAL7024 FINE TEXTURE
Type of fabrics	
Type of fabric Fixscreen	Fibreglass fabric Sergé
Fabric code Fixscreen	FG-SC 3030 CHARCOAL
Confection side	Confection side 1
Technical specs	

Quotation

20042630

10.06.2022

General

Motor position

Pivot 2 (P2)

Blade rotation

Sunprotection

Columns

Mounting base 1A

Invisible reinforced

Mounting holes in the col. 1A

Yes

Direction of water drainage 1A

Pivot

Height water drainage 1A

66 mm

Mounting base 2A

Invisible reinforced

Mounting holes in the col. 2A

Yes

Water drainage direction 2A

Pivot

Height water drainage 2A

66 mm

Mounting base 2B

Invisible reinforced

Mounting holes in the col. 2B

Yes

Water drainage direction 2B

Downwards