



Creating healthy spaces
 NV RENSON ® Sunprotection-Screens SA

Order confirmation

Confirmation date	30.09.2022	CP Interiors
Order number	20229	St. Saviour
Customer number	1001334	28 Rue des Pres. Tr. Est.
Your VAT number		JE2 7QN JERSEY
Currency	GBP	JERSEY
Project reference	LE BRUN SO13479	
Order reference	SO13479	
Latest delivery date	02.12.2022	

Incoterms DAP
 Jersey

Delivery address

CP Interiors
 St. Saviour
 28 Rue des Pres. Tr. Est.
 JE2 7QN JERSEY
 JERSEY

SO13479
 RECEIVED
 16 DEC 2022
 SCANNED
 delivered to
 site 16/12/22
 Lukasz (eagle Transport)

Overview

Material	Quantity	Net amount	VAT %
001000 CAM2 CAMARGUE	1,00 PC	11.398,31	

Total before VAT	11.398,31
VAT	0,00
Total incl. VAT	11.398,31

Free of VAT, export

PAYMENT INFORMATION

Payment term 30 days end of month

For questions or remarks regarding this document, please send an email to outdoor-uk@renson.be

The General Terms and Conditions of Sale are integral part of our agreement. See Professional Portal at <http://www.renson.eu/>



Creating healthy spaces

NV RENSON • Sunprotection-Screens SA

Order confirmation

20229

30.09.2022

Detail

Item	Material	Unit price	Quantity	Gross amount	Discount %	Net amount
001000	CAM2 CAMARGUE		1,00 PC	18.997,18		11.398,31
	Commodity code	94069090	Prefabricated aluminum buildings, sun protection structures			
	Camargue	9.739,00 GBP /	1 PC x 1,00	9.739,00		
	Camargue Line column	522,00 GBP /	1 PC x 3,00	1.566,00		
	Camargue Line reinforced mounting base	208,00 GBP /	1 PC x 3,00	624,00		
				11.929,00	40	7.157,40
	Integrated Fixscreen	1.582,00 GBP /	1 PC x 1,00	1.582,00		
	Integrated Fixscreen	1.983,00 GBP /	1 PC x 1,00	1.983,00		
				3.565,00	40	2.139,00
	UpDown Led : 2x Up RGB + Down White	2.493,00 GBP /	1 PC x 1,00	2.493,00		
				2.493,00	40	1.495,80
	Rain sensor	236,86 GBP /	1 PC x 1,00	236,86		
	Situo 5 IO Pure II - 5-channel transmitter	90,32 GBP /	1 PC x 1,00	90,32		
	Tahoma	198,00 GBP /	1 PC x 1,00	198,00		
	Watertight wall connection (installation profile)	485,00 GBP /	1 PC x 1,00	485,00		
				1.010,18	40	606,11
				7.068,18		4.240,91
	Configuration					
	Protecto prefix (roof 1)		NA			
	Structure					
	Type					
	Structure		Single			
	Location					
	Location		Normal wind loads (standard)			
	Structure strength		Standard			
	Construction					
	Type					
	Roof part		Roof part 1			
	Dimensions					
	Span		2.500 mm			
	Pivot		3.500 mm			
	Passage height		2.250 mm			
	Construction method					
	Span 1		Freestanding			
	Span 2		Freestanding			
	Pivot 1		Freestanding			
	Pivot 2		Full wall			
	Columns					
	Column type 1A		Corner column			
	Column type 2A		Corner column			
	Column type 2B		Corner column			
	Design Styles (TL)					
	Design Styles (SL)					
	Design Style		No			
	Side infills					
	Span 1 (S1)					
	Infill S1		Fixscreen			



Creating healthy spaces

NV RENSON® Sunprotection-Screens SA

Order confirmation

20229

30.09.2022

Pivot 1 (P1)	
Infill P1	Fixscreen
General specifications	
Infill height Fixscreen	Passage height
Comfort	
Lighting	
Position UpDown led	Span 1 + 2
Color led 'UP'	RGB
Color led 'DOWN'	Warm white
Comfort & Design	
Waterproof wall connection	Yes
Automation	
Country of installation	United Kingdom
Motor control	Somfy IO
Renson Connect App	Yes
Frost/Snow function	No
Transmitter	Situo 5 IO Pure II
Rain sensor	Ceramic rain sensor
Voltage motor	230V
Electrical certification	CE (Standard)
Tahoma account	No
Styling	
Colors	
Color type frame and columns	Textured
Color code frame and columns	029/10246-TIGER RAL9016 FINE TEXTURE
Color type of roof blades	Same color as framework
Color of roof blades	029/10246-TIGER RAL9016 FINE TEXTURE
Type of fabrics	
Type of fabric Fixscreen	Fibreglass fabric Natté
Fabric code Fixscreen	NATTE 4503 0202 WHITE
Confection side	Confection side 1
Technical specs	
General	
Motor position	Pivot 1 (P1)
Blade rotation	Sunprotection
Columns	
Mounting base 1A	Invisible reinforced
Mounting holes in the col. 1A	Yes
Direction of water drainage 1A	Pivot
Height water drainage 1A	66 mm
Mounting base 2A	Invisible reinforced
Mounting holes in the col. 2A	Yes
Water drainage direction 2A	Pivot
Height water drainage 2A	66 mm
Mounting base 2B	Invisible reinforced
Mounting holes in the col. 2B	Yes
Water drainage direction 2B	Pivot
Height water drainage 2B	66 mm