Silent Gliss

21-11-22

SO13 800 Blampied.

2x Poles

RECEIVED
21 NOV 2022
SCANNED

SilentGliss

Metropole Measure Sheet - System SG 7630 (SG 6120)

Date of Order: 07/11/2022

Order Reference: SO13800 Blampied

Date Required: As soon as possible

Company Name: CP Interiors

Contact: Tamara

Telephone Number: 01534 768141

Delivery Address: Rue des Pres Trading Estate, St Saviour, Jersey JE2 7QP

Site Contact:

Telephone Number:

Customer Signature:

Colour	Qty	Overall Length	**Installation Height Child Safety Legislation - EN 13120	******Finial Flush Stud other please specify	Size Given is Including (Inc) or Excluding (Exc) Finials	Cord Colour B or W	Input T or F ****Top (6151) or Face (11208) Standard Fixing brackets	Bracket number if known or projection in mm	Cord Drop	Pole Supplied ***Bent or Straight	Glider Type: Standard 11301	Glider Type: *****Wave 60mm	Glider Type: *****Wave 80mm	Glider Type: Other Please specify	Method LH / RH / Pair or Centre Stacking	Input LH / RH or B * Left / right or both side operation	Location
Matte White	1	2130		Flush	Including	W	F			Straight	11301				LH		Living Room
Matte White	1	2500		Flush	Including	W	F			Straight	11301				RH		Living Room

Please Note:
For multiple stack please include diagram
*** If B for both, intermediate pulley will be added at extra cost**
**** If Installation Height is known, cord drops will comply with EN13120**

***** If bent poles required, 11209 brackets will be supplied as standard. Please confirm if a plot or template will be supplied.**
****** If finials required 20335 top fix brackets will be supplied**
******* If Face fix 11207 bracket = 60mm**
If Face fix 11208 bracket = 80mm
********Only Flush or Stud Endcaps available on chrome finish**

Any additional Notes - Please ensure all text is visible

Child Safety Legislation - EN 13120

Operating loop for Child Safety Device			Operating loop for cord retainer	
Installation height	Chain Length		Installation Height	Cord length
Known	Distance from floor to bottom of pull cords shall be at least 0.6m		Known	Distance from floor to bottom of operating chain shall be at least 1.5m
Unknown	Less than or equal to 2/3rd drop of the blind		Not Known drop ≤ 2.5m	length of operating chain loop shall be ≤ 1m
			Not known drop > 2.5m	Shall be ≤ drop of blind less 1.5m