

**SURVEY CHECKLIST: \*\*\*to be completed on site\*\*\***

- Point A to be at midpoint of ridge.
- All lower fitting points should be fixed to the top of plasterboard.
- Corner points F/J/M/C to be on the South/North facing side.
- Point Y/Z to be taken from the vent opener screw with the window in the closed position as per inset photo.
- Points D/E/L/K to be set at 520mm away from the glazing bar.
- Points H/G/B/N to be set at 620mm away from the glazing panel midpoint.

**Confirmation required for the following:**

- Colour of Fabric .....
- Colour of Fittings .....
- (Please note white & gold fittings carry a surcharge of £2+VAT per sail corner.)

**Notes:**

Survey points to be taken from point on conservatory where eye plates are to be fixed.

**MARK ALL POINTS BEFORE COMMENCING SURVEY**

Dimensions should be taken as accurately as possible ideally +/-5mm

Design Shows:  
4 x Made to Measure InShade Sails - ISX - TBC  
(Sails are shown in Ivory for design clarity)

Obstructions: Openers

Special Fittings: None

t : 01786 450083 e : inshade@shadeplus.co.uk

Project: 72292-9807-Grocott

Date: 26.05.23 Drawn: AB Check: --

**Required Dims :**

Sail 01	Sail 02	Sail 03	Sail 04
AB .....	AE .....	AH .....	AL .....
BC .....	EF .....	HJ .....	LM .....
CD .....	FG .....	JK .....	MN .....
DA .....	GA .....	KA .....	AA .....
BD .....	EG .....	HK .....	AM .....
AC .....	AF .....	AJ .....	LN .....
		AY .....	AZ .....
		JY .....	LZ .....
		KY .....	MZ .....

