

Metropole Measure Sheet - System SG 7630 (SG 6120)

Date of Order: CP INTERIORS

Order Reference: SO17050 & SO17142

Date Required: 04/11/2025

Company Name:

Contact:

Telephone Number:

Delivery Address:

Site Contact:

Telephone Number:

Customer Signature:

Colour	Qty	Overall Length	**Installation Height Child Safety Legislation - EN 13120	*****Finial		Size Given is Including (Inc) or Excluding (Exc) Finials	Cord Colour B or W	Input T or F		Bracket number if known or projection in mm	Cord Drop	Pole Supplied		Glider Type		Method LH / RH / Pair or Centre Stacking	Input LH / RH or B * Left / right or both side operation	Location				
				Flush	Stud other please specify			***Top (6151) or Face (11206) Standard Fixing brackets	***Bent or Straight			Standard 11301	****Wave		Other Please specify							
													60mm	80mm								
BRONZE	1	2050	2350	STUD	EXCLUDING	WHITE	FACE	✓			STRAIGHT	✓			YES	✓	LEFT	✓	LEFT	✓	Bed 4 - SMITH	
BRONZE	1	3150	30	2350	STUD	EXCLUDING	WHITE	FACE	✓		STRAIGHT	✓			YES	✓	RIGHT	✓	RIGHT	✓	Bed 4 - SMITH	
BRONZE	1	1900	2630	STUD	EXCLUDING	WHITE	TOP	✓			STRAIGHT	✓			YES	✓	LEFT	✓	LEFT	✓	Bed 3 - SMITH	
BRONZE	1	1600	2630	STUD	EXCLUDING	WHITE	TOP	✓			STRAIGHT	✓			YES	✓	RIGHT	✓	RIGHT	✓	Bed 3 - SMITH	
BRONZE	1	1400	2630	STUD	EXCLUDING	WHITE	TOP	✓			STRAIGHT	✓			YES	✓	RIGHT	✓	RIGHT	✓	Bed 3 - SMITH	
BRONZE	1	1130	2630	STUD	EXCLUDING	WHITE	TOP	✓			STRAIGHT	✓			YES	✓	RIGHT	✓	RIGHT	✓	Bed 3 - SMITH	
BLACK	1	4000	NO CORD, HAND	FLUSH	INCLUDING	NONE (HAND)	TOP	✓			STRAIGHT	✓	YES	✓								BAR NAUTIQUE

Julian Smith

BAR NAUTIQUE

Please Note:
 For multiple stack please include diagram
 * If B for both, intermediate pulley will be added at extra cost
 ** If Installation Height is known, cord drops will comply with EN13120
 *** If bent poles required, 11209 brackets will be supplied as standard. Please confirm if a plot or template will be supplied.
 **** If finials required 20335 top fix brackets will be supplied
 ***** If Face fix 11207 bracket = 60mm
 If Face fix 11208 bracket = 80mm
 *****Only Flush or Stud Endcaps available on chrome finish

Any additional Notes - Please ensure all text is visible

Child Safety Legislation - EN 13120		Operating loop for cord retainer	
Operating loop for Child Safety Device	Chain Length	Installation Height	Cord length
Known	Distance from floor to bottom of pull cords shall be at least 0.6m	Known	Distance from floor to bottom of operating chain shall be at least 1.5m
Unknown	Less than or equal to 2/3rd drop of the blind	Not known drop ≤ 2.5m	length of operating chain loop shall be ≤ 1m
		Not known drop > 2.5m	Shall be ≤ drop of blind less 1.5m

*Tawara checked
04/11/25*

Staff Name Adrian

Order No Surveyor
Measurer

Contact Address

Customer Ref

Date
09-10-2025

Time
12:30 PM

Account Manager:

Notes : jules smith

Location	Supplier	Blind Type /Description	Colour	Qty	Width	Drop	Fitting Height	B or R	Controls	Brackets	Surface	Unit Price
Bed 4		Roman (inside Rec)			1430	1425		B/S	RHM			
		* hit forward in case roller added.										
		80mm wave			3150	2350	F/D	FACE	RHS ↗	SKOPAS	Laon	
		" "			2050	2350	F/D	FACE	LHS ↙		dasmine	
en suite		roller novatec			915	2150		B/S	LHC			
		transparent coat + fascia as previous										
Boat		Upholstery			1100	1800	x 50mm		75mm?			
Seat					550	1000	x 50mm					
Bed 3		80mm wave			1900	2640	F-C (top)	LH		SKOPAS	Laon	Impala
					1600	2630	F-C (top)	RH				
					1400	2630	F-C (top)	RH				
					1130	2630	F-C (top)	RH				

Comments:
All BRONZE silent gliss
30mm metro.

Surface Fixing
C=Concrete
W=Wood
M-Metal
B=Brick
P-Plastic
T=Tile

Order

Customer Signature
X
I have checked and agree with the above choices

Quote

Target Fitting Date
