



Please send to:

order@markilux.com

Your contact	Reference	Customer no.	Order date	Requested delivery date (despatch date)
RAINBOW	GC 6560TRODDEN	55830	09/06/23	15/07/23 IF POSSIBLY

On the basis of your terms and conditions for markilux awnings we hereby place the following order:

Model	Quantity	Overall awning width M [cm]	Extension H [cm]					Frame colour	Front panel colour <sup>1)</sup>	K
			150	200	250	300	350			
markilux MX-2			<input type="radio"/>	<input type="radio"/>	<input type="radio"/>	<input type="radio"/>	<input type="radio"/>			<input type="radio"/>
markilux MX-3	1	3500	<input type="radio"/>	<input type="radio"/>	<input type="radio"/>	<input checked="" type="radio"/>	<input type="radio"/>	HAVANA BROWN 5229		<input type="radio"/>
markilux 970			<input type="radio"/>	<input type="radio"/>	<input type="radio"/>	<input type="radio"/>	<input type="radio"/>			<input type="radio"/>

1) If left blank: supplied in the frame colour. The standard colours and additional colours can be combined as shown in the sales manual. In the case of the markilux MX-3 the front panel colour and end cap styling colour are always the same.

K Improved corrosion protection

## Fabric pattern

SUNBOW 4176Z

Operation side (as viewed from the outside) left  right Radio-controlled motor 868 Mhz io  433 Mhz RTS Radio remote control 1 channel  5 channels 

(io: markilux io-designcontrol (RTS: Situo RTS Pure))

radio control light sensor Sunis WireFree II io 8272086 radio control wind sensor Eolis WireFree io 8272193 radio control wind sensor Eolis io with connection for rain sensor Or 8272328 radio control light and wind sensor Soliris Sensor RTS 8272089 radio control light and wind sensor Soliris Sensor RTS 8272127 

with rain sensor connection

radio control wind sensor Eolis Sensor RTS 8272090 rain sensor Ondeis 230 V 8272065 Wind sensor markilux vibrabox RAL 7043  RAL 9016 

(io/RTS) (8272366 / 8272364) (8272367 / 8272365)

Hard-wired motor Power supply cable with Hirschmann plug connector 5m  10m<sup>2)</sup> 

2) only available for radio-controlled motors

## Manual operation

Crank handle length 110 cm  140 cm  160 cm  180 cm  220 cm spring-assisted operation 

## Notes

## Shadeplus markilux 970

(height 170 cm; maximum awning size 500 × 300 cm / 600 × 250 cm)

Gearbox operation  Motor (io / RTS / hard-wired) Operation side (in case of differing) left  right shadeplus fabric pattern (if it differs from the awning):  
plain material, transolair, vuscreen or Soltis Perform 92

## Fixture

Face fixture bracket face fixture bracket with spreader plate A face fixture bracket with spreader plate B face fixture using spreader plate C (only for the markilux 970) markilux panel 250 mm  continuous top fixture brackets eaves fixture brackets 150 mm  270 mm additional spreader / backing plate for eaves fixture (75383.) Supply brackets in advance 

LED lighting (radio-controlled operation: on / off / dimmable)

LED Line in the cassette LED Spots underneath the cassette Wall sealing profile MX-3 in the same width as the awning<sup>3)</sup> Wall sealing profile MX-3 in standard width = M - 311 mm 

Accessories (please refer to the sales manual / price list) Order no. Quantity

3) On-site width correction necessary in accordance with the actual bracket position!

N.B! Please check your order confirmation! We deliver as confirmed, complaints will not be accepted at a later date!

9915 / 9910

211217