



Fabric Flare complete flameproofing solutions™

Fabric Flare Solutions Ltd
44 Pinbush Road
Lowestoft, Suffolk
NR33 7NL
United Kingdom

Telephone: +44 (0)1502 711211
Email: info@fabricflaresolutions.co.uk
Website: www.fabricflare.co.uk



CERTIFICATE OF TREATMENT

Certificate number: 19761
Date of issue: 05/03/2026
Report reference: 01595.26
Job reference: 97872
Customer reference: 27396 Whitworth

Customer: Posner Interiors
98 George Lane
South Woodford
London
E18 1AD

PRODUCT DESCRIPTION

25.00 Linear Metre **Colefax and Fowler Otto J0293-07 col. Biscuit - Tan and Beige two-tone textured plain woven fabric**
(100% solution-dyed polyester)

TREATMENT

In accordance with the customer's requirements, the product was treated with a flame retardant formulated by Fabric Flare Solutions Limited.

PROCEDURE PRIOR TO IN-HOUSE ASSESSMENT

A test piece of the product was cut and the weight of the sample recorded in terms of g/m². The remainder was FR treated and dried in a baker at the relevant temperature. A further sample of identical measurement was taken from the treated length and weighed to determine the increase in dry pick-up.

IN-HOUSE ASSESSMENT

The treated sample was subjected to a single flame ignitability test replicating, as far as possible, the requirement specified in EN ISO 11925-2. The flame was applied for 15 seconds to the bottom edge of the vertically positioned sample, and no flaming beyond 150mm of the ignition source was observed.

RESULTS

Based on the increase in dry weight and the reaction to the single flame ignitability test, the sample indicated compliance with all the requirements of **02 - BS 5852: Part 1: 1979 (Ignition Sources 0 & 1)**.

Certificate authorised by:

Signature 

PLEASE NOTE

1. Our in-house tests provide an indication of compliance with verification via an independent laboratory if required.
2. For the purposes of CE marking, and/or compliance with the pan European CPR, we can arrange thirdparty verification of FR conformity via an independent, accredited laboratory. Please ask for further details.
3. No liability will be accepted by Fabric Flare Solutions Limited for any changes in appearance, quality or flammability, if the FR treated product is subjected to processing of any kind by others
4. Due to on-going changes in fire test method we recommend the relevance and validity of this Certificate is reconsidered after a period of three years.