

				£	p	
		Supply and install curtain track system: as manufactured by Silent Gliss: 6101 anodised aluminium room divider system or equal and approved, with Silent Gliss 6650 Anti Ligature hangers: include for Nylon glider hooks, reference 6147, fitted to track and dust cover reference 6110 PVC Allow for all system components, complete with suspension rods, hangers, wall brackets, runners, bends noggings, and all components as required by the manufacturer: lateral supports to be integrated with the suspension system: installed in strict accordance with the manufacturers printed instructions: all in accordance with Specification Clause N10/230				
320016A	A	Curtain Track: complete with nylon glider hooks at 10no per metre to beds; maximum floor to ceiling height 2.70m; all in accordance with drawings	125	m	55.00	6875.00
320016C	B	Extra over for wall abutments: include for all wall brackets, supports, etc; wall brackets reference 6503, approximately 75 x 150mm	38	no	39.95	1518.10
320016D	C	Extra over for 90 degree bend	27	no	15.00	405.00
320016F	D	Extra over for 45 degree bend	4	no	15.00	60.00
320016G	E	Extra over for intersections	10	no	18.65	186.50

To Collection £

9044.60

				£	p	
3200170	A	<p>Supply and install roller blind as manufactured by Silent Gliss or equal and approved: SC series roller system or equal and approved: moncontrol chain and rotation elements to suit 89mm louvre width with single draw and stack for widths up to 1200mm, and split draw over 1200mm wide; fabric to be chosen from Silent Gliss price group 3, fabric to be treated with approved fire retarding system;; Manual operations; colour to be confirmed; Include wall fixings, brackets, supports, chain, fittings, clamps, end covers and accessories etc; to be installed in strict accordance with the manufacturers printed instructions; all in accordance with specification clause N10/240</p> <p>Roller blinds; generally</p> <p>to suit window approximately 1010mm wide x 1800mm blind drop</p>	26	no	274.16	7128.16
3200180	B	<p>Mirrors; to be free from tarnishing, discolouration, scratches and other defects visible in the designed viewing conditions; reflection to be undistorted; Polypropylene safety film backing and fixed using screws, inset from corner 50 x 40; edges to be square profiled and ground; secure backing appropriate to mirror size and weight; to be installed in strict accordance with the manufacturers printed instructions; all in accordance with the specification</p> <p>Wall mounted</p> <p>approximately 1220 mm high x 600mm wide; as per specification clause N10/270</p>	17	no		

To Collection £

7128.16