* Discount 60% *

SilentGliss

Curtain Track Measure Sheet

Date of Order: 07/11/18

Order Reference: RA5409

Date Required: ASAP

Company Name: Rainbow Blinds

Contact: Allison

Telephone Number:

Delivery Address: Canyon Road

Site Contact:

Telephone Number:

Customer Signature:

System Number	Colour	Qty	* Child Safety Device (Integral 10483) Y / N	Overall Width	Location	** Installation Height:	Input LH / RH or B *** Left / right or both side operation	Input T / F or A Top or Face fixing or Adjustable brackets	Bracket number if known or projection in mm	Method LH / RH / Pair or Centre Stacking	Cord Drop	Wave Tracks please tick If face 3135 bkt = 60mm 3136 bkt = 80mm 60mm	80mm
6100	White	1	—	10900	First Floor	N/A	LH	T	—	LH.	N/A	☐	☑
6100	White	1	—	10900	First Floor	N/A	LH	T	—	LH.	N/A	☐	☑
												☐	☐
												☐	☐
												☐	☐
												☐	☐
												☐	☐
												☐	☐
												☐	☐

Please Note: For multiple stack please include diagram
60mm Wave uses 3135 bracket as standard
80mm wave uses 3136 bracket as standard
* Child Safety Device applicable to System 3840 only complete with Silent Gliss Colorama Wave Curtains only
** If the Installation Height is known - cord drops will comply with EN13120
*** If B for both, intermediate pulley will be added at extra cost

* Order to follow for curtains once drop confirmed *

Child Safety Legislation EN 13120

Operating loop for Child Safety Device		Operating loop for chain retainer	
Installation Height	Chain Length	Installation Height	Chain Length
Known	Distance from floor to bottom of pull cords shall be at least 0.6m	Known	Distance from floor to bottom of operating chain shall be at least 1.5m
Unknown	Less than or equal to 2/3rd drop of the blind	Not Known drop ≤ 2.5m	Length of operating chain loop shall be ≤1m