

ORDER

Please send to:

order@markilux.com

Your contact: Rainbow Business Reference to: ED 4999 Bolton Customer no.: 55830 Order date: 11-06-24 Requested delivery date (despatch date): ASAP

On the basis of your terms and conditions for markilux awnings we hereby place the following order:

| Model | Quantity | Overall awning width M [cm] | Extension H [cm] | | | | | Frame colour | Front panel colour ¹⁾ | K |
|---------------|----------|--------------------------------|-----------------------|-----------------------|----------------------------------|-----------------------|-----------------------|--------------|----------------------------------|-----------------------|
| | | | 150 | 200 | 250 | 300 | 350 | | | |
| markilux MX-2 | | | <input type="radio"/> | <input type="radio"/> | <input type="radio"/> | <input type="radio"/> | <input type="radio"/> | | | <input type="radio"/> |
| markilux MX-3 | 1 | 2750 | <input type="radio"/> | <input type="radio"/> | <input checked="" type="radio"/> | <input type="radio"/> | <input type="radio"/> | 5215 | 5215 | <input type="radio"/> |
| markilux 970 | | | <input type="radio"/> | <input type="radio"/> | <input type="radio"/> | <input type="radio"/> | <input type="radio"/> | | | <input type="radio"/> |

¹⁾ If left blank: supplied in the frame colour. The standard colours and additional colours can be combined as shown in the sales manual. In the case of the markilux MX-3 the front panel colour and end cap styling colour are always the same.

K Improved corrosion protection

Fabric pattern

Operation side (as viewed from the outside)

left right

Radio-controlled motor

868 Mhz io 433 Mhz RTS

Radio remote control

1 channel 5 channels

(io: markilux io-designcontrol / RTS: Situo RTS Pure)

radio control light sensor Sunis WireFree II io

8272086

radio control wind sensor Eolis WireFree io

8272193

radio control wind sensor Eolis io with connection for rain sensor OI

8272328

radio control light and wind sensor Soliris Sensor RTS

8272089

radio control light and wind sensor Soliris Sensor RTS

8272127

with rain sensor connection

radio control wind sensor Eolis Sensor RTS

8272090

rain sensor Ondeis 230 V

8272065

Wind sensor markilux vibrabox

RAL 7043 RAL 9016

(io/RTS)

(8272366 / 8272364)

(8272367 / 8272365)

Hard-wired motor

Power supply cable with Hirschmann plug connector

5m 10m ²⁾

²⁾ only available for radio-controlled motors

Manual operation

Crank handle length 110 cm 140 cm 160 cm 180 cm 220 cm

spring-assisted operation

Notes

Shadeplus markilux 970

(height 170 cm; maximum awning size 500 x 300 cm / 600 x 250 cm)

Gearbox operation

Motor (io / RTS / hard-wired)

Operation side (in case of differing)

left right

shadeplus fabric pattern (if it differs from the awning):
plain material, transolair, vuscreen or Soltis Perform 92

Fixture

Face fixture bracket

face fixture bracket with spreader plate A

face fixture bracket with spreader plate B

face fixture using spreader plate C (only for the markilux 970)

markilux panel

250 mm

continuous

top fixture brackets

eaves fixture brackets

150 mm

270 mm

additional spreader / backing plate for eaves fixture (75383.)

Supply brackets in advance

LED lighting (radio-controlled operation: on / off / dimmable)

LED Line in the cassette

LED Spots underneath the cassette

Wall sealing profile MX-3 in the same width as the awning ³⁾

Wall sealing profile MX-3 in standard width = M - 311 mm

Accessories (please refer to the sales manual / price list)

Order no. Quantity

³⁾ On-site width correction necessary in accordance with the actual bracket position!

N.B! Please check your order confirmation! We deliver as confirmed, complaints will not be accepted at a later date!

9915 / 9910

211217

Folding-arm cassette awning | markilux MX-2 / MX-3 / 970