



Please send to:

order@markilux.com

Your contact: **Rainbow Blinds** Reference: **RAIN 8132 GILBERT** Customer no.: **55830** Order date: **04-06-24** Requested delivery date (despatch date): **ASAP**

On the basis of your terms and conditions for markilux awnings we hereby place the following order:

Model	Quantity	Overall awning width		Extension H [cm]					Frame colour	Front panel colour <sup>1)</sup>	K
		M [cm]		150	200	250	300	350			
markilux MX-2				<input type="radio"/>	<input type="radio"/>	<input type="radio"/>	<input type="radio"/>	<input type="radio"/>			<input type="radio"/>
markilux MX-3	1	520		<input type="radio"/>	<input type="radio"/>	<input type="radio"/>	<input type="radio"/>	<input checked="" type="radio"/>	5215	5215	<input type="radio"/>
markilux 970				<input type="radio"/>	<input type="radio"/>	<input type="radio"/>	<input type="radio"/>	<input type="radio"/>			<input type="radio"/>

<sup>1)</sup> If left blank: supplied in the frame colour. The standard colours and additional colours can be combined as shown in the sales manual. In the case of the markilux MX-3 the front panel colour and end cap styling colour are always the same.

**K** Improved corrosion protection

**Fabric pattern**

31008

**Operation side (as viewed from the outside)**

left  right

**Radio-controlled motor**

868 Mhz io  433 Mhz RTS

**Radio remote control**

1 channel  5 channels

(io: markilux io-designcontrol / RTS, Situo RTS Pure)

radio control light sensor Sunis WireFree II io

8272086

radio control wind sensor Eolis WireFree io

8272193

radio control wind sensor Eolis io with connection for rain sensor

8272328

radio control light and wind sensor Soliris Sensor RTS

8272089

radio control light and wind sensor Soliris Sensor RTS

8272127

with rain sensor connection

radio control wind sensor Eolis Sensor RTS

8272090

rain sensor Ondeis 230 V

8272065

Wind sensor markilux vibraBox

RAL 7043

RAL 9016

(io/RTS)

(8272366 / 8272364)

(8272367 / 8272365)

**Hard-wired motor**

**Power supply cable with Hirschmann plug connector**

5m  10m <sup>2)</sup>

<sup>2)</sup> only available for radio-controlled motors

**Manual operation**

Crank handle length 110 cm  140 cm  160 cm  180 cm  220 cm

spring-assisted operation

**Notes**

**Shadeplus markilux 970**

(height 170 cm; maximum awning size 500 x 300 cm / 600 x 250 cm)

Gearbox operation  Motor (io / RTS / hard-wired)

Operation side (in case of differing)

left  right

shadeplus fabric pattern (if it differs from the awning):

plain material, transolair, vusgreen or Soltis Perform 92

**Fixture**

Face fixture bracket

face fixture bracket with spreader plate A

face fixture bracket with spreader plate B

face fixture using spreader plate C (only for the markilux 970)

markilux panel 250 mm

continuous

top fixture brackets

eaves fixture brackets 150 mm

270 mm

additional spreader / backing plate for eaves fixture (75383.)

Supply brackets in advance

LED lighting (radio-controlled operation: on / off / dimmable)

LED Line in the cassette

LED Spots underneath the cassette

Wall sealing profile MX-3 in the same width as the awning <sup>3)</sup>

Wall sealing profile MX-3 in standard width = M - 311 mm

Accessories (please refer to the sales manual / price list) Order no. Quantity

<sup>3)</sup> On-site width correction necessary in accordance with the actual bracket position!

**N.B!** Please check your order confirmation! We deliver as confirmed, complaints will not be accepted at a later date!