



WINDOWTECHS FIRE CURTAINS

QUOTATION

GST No:06AABCW1291M1Z3	Window Techs India Pvt. Ltd.
PAN:AABCW1291M	Plot No 805, Sector-69 IMT Faridabad
Account No:50200044688712	Phone: 9790914681/ 0129-4031093
IFSC:HDFC0001568	Enquiry No:- WT 076
Email:info@windowtechs.in	Date :28/08/2024
To, Mr.Kunal Arora	Project : DXC Noida

Automatic Fire Curtains Supply, Installation, Testing & Commissioning (SITC)

Supply installation testing and commissioning of Fire Curtains with Galvanized MS powder coated head top box of suitable size, Powder coated side guides (100mm x 50 mm) and bottom bars with Gravity fail safe DC motors one per roller for curtain up operation with standard battery back-up fixed into 76/88 mm steel rollers with FAB690PU fabric must be according to DIN EN 13501-1 and stainless steel reinforced glass fibre with fire-retardant aluminum pigmented polyurethane coating, with its control panel and all installation assemblies & accessories required to complete the installation. The operation shall be suitable for dedicated 230 volts UPS, 50 Hz AC supply. Complete system tested in accordance with EN 1634-1 and EN 12101-1 (for minimum 120 minutes integrity & tested at 1000°C) with CE certificate from European Notified Body. Both test reports EN 1634-1 & EN 12101-1 must be according to the requirement of particular project, if single roller curtain is there then single roller certificates and double roller curtain is there then double roller certificates must be submitted accordingly. The fire curtain must be according to Classification of Fire Resistance Performance in Accordance with EN 13501-2: 2016. The manufacturer's valid EN certification for oversized fire curtains according to EN 15269-11 covering the sizes of offered fire curtains as per BOQ, should be available. Each Fire Curtain shall have independent control Panel suitable for 230V AC supply, provision to integrate with Fire signal, and battery backup. The emergency retract switch shall be provided on both sides of curtain. The Fire curtain shall reset automatically when fire control panel is reset. Fabric and all components sourced from the original manufacturer who has valid type test certificate of the fire curtain and third-party quality surveillance audit as per above standards including oversize certification according to applicable EN standards. The scope also includes fabrication, supply and installation of closed MS sections corner supports for fixing side channels, design suitable for stability and integrity with two hours fire rating, wherever required for full height of Fire curtain, as per approved design, duly finished with powder coating of finish matching to side channels of fire curtains. All the required test / certificates must be less than 5 Years validity. No mirror certificates allowed

Installation: The fire curtain has fixing options to suit all types of ceiling configurations and can be integrated into either a suspended or a solid ceiling. It remains hidden until required. Upon receiving a signal from the fire detection system or on loss of power with the gravity fail safe system, the curtain automatically unwinds to its operational position.

Sl.No.	Item Description	Unit	Quantity	Rate	Amount
LOWER GROUND FLOOR					
1	Automatic Fire Curtain Width: 6970 mm , Height: 2700 mm	Nos	1.00	3,70,000.00	3,70,000.00
2	Automatic Fire Curtain Width: 2330 mm , Height: 2700 mm	Nos	1.00	1,60,000.00	1,60,000.00
FIRST FLOOR					
1	Automatic Fire Curtain Width: 1300 mm , Height: 2700 mm	Nos	1.00	1,60,000.00	1,60,000.00
2	Automatic Fire Curtain Width: 1198 mm , Height: 2700 mm	Nos	1.00	1,60,000.00	1,60,000.00
3	Automatic Fire Curtain Width: 14695 mm , Height: 3000 mm	Nos	1.00	7,23,750.00	7,23,750.00
SUB TOTAL					15,73,750.00
GST - 18%					2,83,275.00
Sub Total					18,57,025.00

Terms & Conditions:

1. Payment Term: 50 % Advance against PO and 50% before material dispatching
2. Delivery within 4-5weeks from date of release of purchase order approved drawing and advance payment.
3. Scaffolding support to hang the curtain will be provided by the client
4. However any civil work/civil modification location to install the curtain to be done by client
5. Installation is also included in the above price
6. Power supply for installation to be provided by client
7. All goods will remain the property of WindowTechs until paid for in full. We reserve the right to remove any units fitted by ourselves or others until full payment is received.
8. This quote is valid for 60 days only
9. As per Section 16 of the MSME Act, the buyer is liable to pay interest with the monthly rests to the supplier in case of non-payment or delayed payment. The interest is compounded at the rate of 24%.

Regards,

For Window Techs India Pvt.Ltd

Alistair Paiva